

# High-purity gas bursting discs

## Benefits

- Individual product specification for material, pressure and dimension
- Maximum leak-tightness, absence of particles and minimum leak rates
- Space-saving installation
- The VCR screw coupling remains undamaged after bursting



High-purity gas bursting disc  
in VCR coupling

## Description

Berstscheiben Schlesinger has developed high-purity gas bursting discs for VCR systems, particularly for satisfying the highest requirements regarding leak-tightness, cleanliness and resilience.

We offer our customers standard versions of high-purity gas bursting discs in the form of rupture discs or scored reverse-buckling bursting discs. Our high-purity gas bursting discs are completely made of metal and are produced without the use of polymers. They are particularly known for their vacuum resistance and vacuum tightness.

\*Inconel and Hastelloy are registered trade names.

## Function

High-purity gas bursting discs are, for example, used in gas cabinets. The bursting disc reliably bursts when excessive overpressure is generated during the gas-mixing process and safely releases the overpressure.

**Only the bursting disc without the screw coupling must be exchanged after bursting.**

## Installation

High-purity gas bursting discs are installed in VCR screw couplings instead of sealing discs.

## Technical data

General remarks	
Configuration	domed, scored, fragment-free opening
Media	gas, steam, liquid (gas cushion is required)
Temperature range	-80°C to +450°C
Tolerance of burst pressure	±10% (±5% on request)
leak rates	<10E-9 mbar x L/sec

Materials	
Stainless steel	standard application
Nickel	for lowest pressures
Inconel*	for high temperatures
Hastelloy*	esp. corrosion-resistant

\* Special materials on request.

Minimum bursting pressure in barü at 20 °C			Free cross-section[mm <sup>2</sup> ]
NPS	Nickel	Stainless steel	excessive pressure
¼"	10	25	17
½"	5	20	23
¾"	3	10	143
1"	2	5	283

\*Special materials on request

Dimensions	
Bursting disc	VCR coupling
12,5 mm	¼ inch
20 mm	½ inch
35 mm	1 inch

Certifications
CE marking according to Directive 2014/68 EU
QM-system according to ISO 9001:2015